



**3472 Highway 5
Douglasville, GA 30135
770-942-0118**

"Your Leader in Backyard Vacation Fun"

SPRING OPENING

Mineral Springs / Aqua Logic

1. Remove cover and store using BioGuard **Stow Away**. (see Stow Away procedure)
2. Remove the winter plugs from the pool returns and replace them with directional eyeballs or automatic cleaner fittings.
3. Replace the pump plugs, filter cap, chlorinator drain plug, heater plug, and any other plugs that were removed to drain water from the filter system.
4. Remove the gizmo or winter plug from the skimmer and replace the skimmer basket.
5. Raise the water level in the pool to half way up the skimmer faceplate.
6. Prime the pump by removing the pump strainer housing lid and fill the pump strainer housing with water. Replace the lid and turn on the pump. If it fails to prime after 2-3 minutes, repeat this procedure until water stays in the pump strainer housing.
7. Backwash and clean sand filter with BioGuard **Strip Kwik** if the filter was not chemically cleaned before winterizing. If sand has not been changed in three or more years, change the sand before starting up the season.
 - Or Clean or replace the cartridge(s) in cartridge filters using BioGuard **Strip Kwik**
 - Or Backwash DE filter and recharge with DE powder through the skimmer.
8. Allow pool water to circulate 24 to 48 hours before testing and balancing alkalinity, pH and calcium hardness. Bring water sample to Brown's Pools and Spas for complete water analysis.
9. Perform the Minerals test to determine how much Mineral Springs Beginnings will be needed to start up. Boost mineral level up to 3,000 ppm using _____ lbs.
10. Balance pH, alkalinity and calcium hardness.
11. Add _____ oz. Backup Algaecide
12. Shock pool using _____ bag(s) Smart Shock
(This should be done at night for maximum performance)
(Double Shock for Green Water)
13. Add Stingy Sticks to Chlorinator or _____ Smart Sticks to Skimmer basket
14. Add _____ oz. Polysheen Blue

During high bather loads, large amounts of rain or cloudy water, put the main switch in the SANITIZER BOOST position for 24 hours. Pur switch back to "AUTO" position.

Brown's Pools Water Analyst

Date of Analysis